

CORTEM GULF Fzco

Regional Head Office
RA08AB06, Jebel Ali Free Zone
P.O. Box 17123, Dubai, UAE
Tel: 00971- 4 - 806 2000
Fax: 00971- 4 - 806 2001
Email: info-gulf@cortemgroup.com
Web: www.cortemgroup.com



To be sure to be safe.

Messrs DELTA GmbH	Data 17-10-2024
To the attention of Farshad Shoarian	Your Reference : RFQ for LCP & JB - PR 200- CORTEM
	Zone Agent

COMMERCIAL OFFER DELTA GmbH

PROJECT : NA
END-USER : NA
LOCATION : UAE
MATERIAL : EX LIGHTING FIXTURE
RFQ REF : CG2024_0991

COMMERCIAL TERMS AND CONDITIONS

OFFER VALIDITY:	30	days from d.o.	TYPE OF PACKING:
PRICES:	NET	IN	EUR
DELIVERY POINT 1:	EX WORKS JAFZA		
DELIVERY POINT 2:			

PAYMENT TERMS:	100% along with the Purchase Order
----------------	------------------------------------

DELIVERY:	4-5 working weeks from that date of PO and approved GA drawing
-----------	--

OFFER TOTAL AMOUNT

Total Amount of Goods	12,600.00
Spare Parts for Start-up	0.00
Documentation Charges	0.00
Packing	0.00
Total Amount of Goods EX-Works	0.00
Amount	0.00
Amount	0.00
Total Amount of Quotation	12,600.00
Spare Parts for 2 Years	0.00

Technical Reference	Badruddin M. Khan	B.Khan@cortemgroup.com
Commercial Reference	Badruddin M. Khan	B.Khan@cortemgroup.com



ITEM	CODE	DESCRIPTION	U.M.	QTY	UNIT NET PRICE	TOTAL PRICE
1	CTB484820S1	RU001A-LCP-01 & RU001B-LCP-01	NR	2	2,500.00	5,000.00
		<p>Junction box is made in stainless steel 316L. Ex II 2GD Ex deb IIC T Gb Ex tb IIIC T°C Db, IP66. Ambient temperature -20 +55°C. Lid fixed with hinges and screws. 1 removable gland plate: bottom side. External dimension 480x480x205mm. 1xSS mounting plate. 1x Earth bar m5 with 10 holes. 1x SS breather with Lock Nut. 1x Yellow 24V DC Indicating lamp. (Common Alarm Unit) 1x Red 24V DC Indicating lamp. (Common Trip Unit) 1x Green 24V DC Indicating lamp. (Unity Ready to Start) 1x Green 24V DC Indicating lamp.(Compressor Running) 1x Green 24V DC Indicating lamp. (Oil Pump Running) 1x Green Pushbutton with 2NO contact block. (Unit Start) 1x Green Pushbutton with 2NO contact block. (Oil Pump Start) 1x Red Push button with 2NC contact block. (Unit Stop) 1x Red Push button with 2NC contact block. (Oil Pump Stop) 1x Red Emergency Push Button with 4NC contact block. (EM. Stop) 1x Black Push button with 2NO contact block. (Lamp Test) 2x 10A 2 POSITION (L-A/R)Selector switch with external handle. 2x 10A 3 POSITION (H-O-A)Selector switch with external handle. TB-1: 12x2.5sq.mm terminal.(WDU2.5) TB-2: 12x2.5sq.mm terminal.(WDU2.5) TB-3: 12x2.5sq.mm terminal.(WDU2.5) TB-4: 12x2.5sq.mm terminal.(WDU2.5) 1X M40x1.5 Brass Ni-Plated Stopping plug with Lock-Nut 2X M32x1.5 Brass Ni-Plated Stopping plug with Lock-Nut 4X M25x1.5 Brass Ni-Plated Stopping plug with Lock-Nut Cable entry details.(Please confirm the cable entry) 1x41mm hole suitable for M41 cable entry at the bottom. 2x33mm hole suitable for M32 cable entry at the bottom. 4x26mm hole suitable for M25 cable entry at the bottom.</p>				
2	CTB453820S1	JBD-A-RU0001A-01 & JBD-A-RU0001B-01	NR	2	1,400.00	2,800.00
		<p>Junction box made in stainless steel 316L. Ex II 2GD Ex eb IIC T Gb Ex tb IIIC T°C Db, IP66. Ambient temperature -20 +55°C. Lid fixed with hinges and screws. 1 removable gland plate: bottom side. External dimension 450x380x205mm. 1 x SS Mounting Plate. 1 X M8 Earthing stud. 1x Screen bar with earth bolt. 1x M20x1.5 SS SS with Locknut. TB-1: 24x2.5sq.mm terminal.(WDU2.5) TB-2: 21x2.5sq.mm terminal.(WDU2.5) 10X M20x1.5 Brass Ni-Plated Cable Gland with Locknut suitable for armoured cable +Shroud. 2x M20x1.5 Brass Ni-Plated stopping plug with lock-nut. 1x M25x1.5 Brass Ni-Plated stopping plug with lock-nut. 1x M32x1.5 Brass Ni-Plated stopping plug with lock-nut. Cable entry details. (Please confirm the cable entry) 1x33mm hole suitable for M32 cable entry at the bottom. 1x26mm hole suitable for M25 cable entry at the bottom. 12x21mm hole suitable for M20 cable entry at the bottom.</p>				
3	CTB303020S1	JBD-A-RU0001A-03 & JBD-A-RU0001B-03	NR	2	900.00	1,800.00
		<p>Junction box made in stainless steel 316L. Ex II 2GD Ex eb IIC T Gb Ex tb IIIC T°C Db, IP66. Ambient temperature -20 +55°C. Lid fixed with hinges and screws. 1 removable gland plate: bottom side. External dimension 306x306x205mm. 1 x SS Mounting Plate. 1 X M8 Earthing stud. 1x Screen bar with earth bolt. 1x M12x1.5 SS SS with Locknut. TB-1: 12x2.5sq.mm terminal.(WDU2.5) 2X M20x1.5 Brass Ni-Plated Cable Gland with Locknut suitable for armoured cable +Shroud. 2x M20x1.5 Brass Ni-Plated stopping plug with lock-nut. 1x M25x1.5 Brass Ni-Plated stopping plug with lock-nut. 1x M32x1.5 Brass Ni-Plated stopping plug with lock-nut Cable entry details. (Please confirm the cable entry) 1x33mm hole suitable for M32 cable entry at the bottom. 1x26mm hole suitable for M25 cable entry at the bottom. 10x21mm hole suitable for M20 cable entry at the bottom.</p>				
4	CTB262620S1	JBD-A-RU0001A-02 & D-A-RU0001B-02	NR	2	750.00	1,500.00

		<p>Junction box made in stainless steel 316L. Ex II 2GD Ex eb IIC T Gb Ex tb IIIC T°C Db, IP66. Ambient temperature -20 +55°C. Lid fixed with hinges and screws. 1 removable gland plate: bottom side. External dimension 260x260x205mm. 1 x SS Mounting Plate. 1 X M8 Earthing stud. 1x M20x1.5 SS SS with Locknut. 1x Screen bar with earth bolt. TB-1: 16x2.5sq.mm terminal.(WDU2.5) 5X M20x1.5 Brass Ni-Plated Cable Gland with Locknut suitable for armoured cable +Shroud. 2x M20x1.5 Brass Ni-Plated stopping plug with lock-nut 1x M25x1.5 Brass Ni-Plated stopping plug with lock-nut. 1x M32x1.5 Brass Ni-Plated stopping plug with lock-nut. Cable entry details. (Please confirm the cable entry) 1x33mm hole suitable for M32 cable entry at the bottom. 1x26mm hole suitable for M25 cable entry at the bottom. 7x21mm hole suitable for M20 cable entry at the bottom.</p>				
5	CTB262620S1	JBD-A-RU0001A-04 & JBD-A-RU0001B-04	NR	2	750.00	1,500.00
		<p>Junction box made in stainless steel 316L. Ex II 2GD Ex eb IIC T Gb Ex tb IIIC T°C Db, IP66. Ambient temperature -20 +55°C. Lid fixed with hinges and screws. 1 removable gland plate: bottom side. External dimension 260x260x205mm. 1 x SS Mounting Plate. 1 X M8 Earthing stud. 1x M20x1.5 SS SS with Locknut. TB-1: 12x2.5sq.mm terminal.(WDU2.5) 4X M20x1.5 Brass Ni-Plated Cable Gland with Locknut suitable for armoured cable +Shroud 2x M20x1.5 Brass Ni-Plated stopping plug with lock-nut 1x M25x1.5 Brass Ni-Plated stopping plug with lock-nut. 1x M32x1.5 Brass Ni-Plated stopping plug with lock-nut. Cable entry details. (Please confirm the cable entry) 1x33mm hole suitable for M32 cable entry at the bottom. 1x26mm hole suitable for M25 cable entry at the bottom. 6x21mm hole suitable for M20 cable entry at the bottom.</p>				
<p>1) If not specified, any cable entry can be drilled only subject to Cortem's authorization and, in any case, the observance of the instructions on the certificate is mandatory. 2) Any accessory/material/service that is NOT specified in the quotation is NOT included. 3) Delivery time is the best one estimated at the time of quotation. The actual lead time will start from receipt of order and from approval of the relevant drawings from your side. In case of order modification, the lead time will be re-scheduled and a revised order confirmation will be issued by Cortem. 4) The quoted prices are valid for orders placed within the validity of the offer, as specified in the General Terms and Condition of Sale. 5) The quoted prices have been calculated on the basis of the quantities required. In case the order is issued for lower quantities, Cortem reserves the right to revise prices to the new requirements. 6) The General Terms and Conditions of Sale are specified here below.</p>						