

# CERTIFICATE OF MATERIAL

\* According to EN 10204:2004 (E) 3.1

Specification : ASTM A479 TYPE316/316L (STRAIN-HARDENED 2)  
Material Mfr. : YAMASHIN STEEL CO., INC.  
Customer : Aman Engineering  
Project Name :

CAS No. :  
Certificate No. : HD202503-1277  
PO No. : PO-AEE-25-0070  
POR No. : ENER PROCESS FZ- LLC  
Date of issue : Mar-13-2025

HCD No	Description (Part Name)	Q'ty
JLQ	Male Adapter 1/2"OD-1/4 NPT(CAM8-4N)	4 EA

**Chemical Composition(%)**

C	Si	Mn	P	S	Ni	Cr	Mo							
0.030 max	1.00 max	2.00 max	0.045 max	0.030 max	10.00- 14.00	16.00- 18.00	2.00- 3.00							
0.010	0.24	1.64	0.038	0.022	10.06	16.59	2.69							

**Mechanical Properties**

Yield Strength MPa	Tensile Strength MPa	Elongation (%)	Reduction of Area (%)	Hardness ( )
515 min	655 min	25 min	40 min	
687	769	37	70	

Remarks ISSUE No. : -  
 \* Visual & Dimensional Inspection : Good  
 \* Mechanical Tested According to ASTM A370  
 \* Grain Size Result : 5  
 \* Solution Treatment 1060°C WQ  
 \* Micro Test : GOOD  
 \* Macro Test : GOOD  
 \* Intergranular Corrosion Test : Good  
 \* Embrittlement Test (ASTM A262 Practice:E) : GOOD

We hereby certify that the material herein has been made and tested in accordance with the above specification and also with the requirements called for by the above order.

\_\_\_\_\_  
(Customer / Third Party)



\_\_\_\_\_  
Manager of Quality Assurance Dept.