



# ASPC Project



<b>END CUSTOMER</b>	: Arya Sasol Polymer Company
<b>CONTRACTOR</b>	: DYPNF Co., Ltd.
<b>VENDOR NAME</b>	: Airpack Netherlands BV
<b>EQUIPMENT DESCRIPTION</b>	: Screw Compressor & Roots Blower
<b>PURCHASE ORDER NUMBER</b>	: PO-PC2312-08

Customer Document : 3944-VD-0171-DYP-RE-400-LST-0080  
Number

Airpack Document Number : 23383-06

Document Title : I/O List

Review Code and Status		Contractor Initials/Signature	Date signed
<input type="checkbox"/>	<b>Code 1</b> <b>REJECTED</b> - Vendor to revise and Resubmit. Work cannot proceed		
<input type="checkbox"/>	<b>Code 2</b> Comments As Noted - Work May proceed, subject to compliance with and incorporation of comments		
<input type="checkbox"/>	<b>Code 3</b> No Comments - Work may proceed.		
<input type="checkbox"/>	<b>Code 4</b> Information only - Review not required.		

04	Issued for Approval	10-09-2025	SC	SC	JJ
03	Issued for Approval	26-06-2025	SC	SC	JJ
02	Issued for Approval	27-05-2025	SC	SC	JJ
01	Issued for Approval	12-05-2025	SC	SC	JJ
Rev. No.	Description	Date	Prepared by	Checked by	Approved by

# I/O SUMMARY for POWDER Transfer Package

PROJECT : 300 KT POLYETHYLENE PLANT ARYA SASOL POLYMER COMPANY (ASPC)

DESCRIPTION	DI	DO	AI	AO	SUM	REMARK
44C-40001A	3	2	6	0	11	8x RTD
44C-40001B	3	2	6	0	11	8x RTD
44C-80001A	3	2	6	0	11	8x RTD
44C-80001B	3	2	6	0	11	8x RTD
44C-80002A	3	2	4	0	9	8x RTD
44C-80002B	3	2	4	0	9	8x RTD
44C-80004A	3	2	6	0	11	8x RTD
44C-80004B	3	2	6	0	11	8x RTD
44C-80005A	3	2	6	0	11	8x RTD
44C-80005B	3	2	6	0	11	8x RTD
44C-80005C	3	2	6	0	11	8x RTD
<b>TOTAL</b>	<b>33</b>	<b>22</b>	<b>62</b>	<b>0</b>	<b>117</b>	<b>88x RTD</b>

**Note.**

\* It's actual I/O points.

The DCS/ESD System has to have 20% spare points.

## DESCRIPTION and USER'S GUIDE for IO LIST

### 1. General Notes

- 1) This list applies to measurements and devices to be monitored and controlled by the DCS.
- 2) For preparing the measurement List, the following format and description are to be used as guide-lines.

### 2. Format and guide-lines to fill out

NO	TAG NO	SERVICE DESCRIPTION	FROM /TO	RANGE	UNIT	SET POINT				SIGNAL TYPE	PWR SRC	I/O TYPE	CONT -ACT	FUNCTION						INST TYPE	IS/NIS	VALVE ACTION	LOOP TAG NO	JUNCTI ON BOX	P & ID	LOGIC / LOOP NO	REMARK
						LL	L	H	HH					C	I	R	A	Z	SOE								
(1)	(2)	(3)	(4)	(5)	(6)	(7)				(8)	(9)	(10)	(11)	(12)						(13)	(14)	(15)	(16)	(17)	(18)	(19)	(20)

(1) NO : Serial Number

(2) ID NO : Identification Number (20 digits with dash mark)

(3) SERVICE DESCRIPTION

Service description of instrument or device is specified.

(4) FROM/TO (5 digits)

"FROM" means the source of DCS input signal and "TO" means the destination of DCS output signal as follows ;

FLD : FIELD (OR LOCAL)	BC : BATTERY CHARGER
MCC : MOTOR CONTROL CENTER	DG : DIESEL GENERATOR
SG : SWITCHGEAR	PRP : PROTECTION RELAY PANEL
LC : LOAD CENTER	TDP : TRANSDUCER PANEL
CCB : CENTRAL CONTROL BUILDING	TPP : T/L PROTECTION PANEL
LCP : LOCAL CONTROL PANEL	BFP : BREAKER FAILURE PANEL
EPLC : ELECTRIC PROGRAMMABLE LOGIC CONTROLLER	
BPP : BUS PROTECTION PANEL	DP : DISTRIBUTION PANEL
UPS : UNINTERRUPTIBLE POWER SYSTEM	VR : VOLTAGE REGULATOR SYSTEM
ANN : PLANT ANNUNCIATOR SYSTEM	COAL : COAL HANDLING SYSEM
ELE : ELECTRICAL AUX RELAY	DCS : DISTRIBUTED CONTROL SYSTEM
VMS : VIBRATION MONITORING SYSTEM	ESD : EMERGENCY SHUTDOWN
ECMS : ELECTICAL CONTROL AND MONITORING SYSTEM	
PTC : PULSE TIMER CONTROLLER	MCC-VFD : Variable frequency drive located in substation
LCS : LOCAL CONTROL STATION	RLY : INTERPOSING RELAY CABINET

## DESCRIPTION and USER'S GUIDE for IO LIST

(5) RANGE (20 digits)

Process variable range is specified.(for example 300 ~ 10,000)

(6) UNIT (8 digits)

The engineering units used in this list are as follows ;

<u>ORIGINAL UNIT</u>	<u>DESCRIPTION USED</u>	<u>ORIGINAL UNIT</u>	<u>DESCRIPTION USED</u>
bar gage	bar.g (mbar.g)	Megawatt	MW
Vacuum	mbar.a	Hertz	Hz, KHz
°C (Degree C)	°C	Percent	%
millimeter, inch	MM, IN	micro mho/Cm	UMHO
Meter	M	kcal/hour	KC/H
part(s) per million	PPM	revolution per minute	RPM
part(s) per billion	PPB	Ton/Hour	T/H
pH	PH	kg/hour	KG/H
Volt	V	liter/minute	L/M
Kilovolt	KV		
Ampere	A		

(7) SET POINT

This column shows the software threshold value in analog input for alarm or interlock purpose.

- HH : High-High Alarming
- H : High Alarming
- L : Low Alarming
- LL : Low-Low Alarming

(8) SIGNAL TYPE (6 digits)

The type of input/output signal is specified as follows ;

- 4~20mA : 4-20 mA with HART protocol
- NAMUR : NAMUR for proximity switches
- 24V DC : 24V DC binary signals
- VFC : Volt Free Contact

(9) PWR SRC : Power source (1 digit)

The power source of signal is specified as follows ;

- . I : INTERNAL POWER SUPPLIED FROM DCS
- . E : EXTERNAL POWER SUPPLIED FROM OUTSIDE OF DCS

(10) I/O TYPE ( 2 digits)

The signal type of input or output is specified as follows :

- . AI : ANALOG INPUT
- . AO : ANALOG OUTPUT
- . DI : DIGITAL INPUT
- . DO : DIGITAL OUTPUT

- PT 100Ω

(11) CONTACT : Contact type (2 digits)

The status of digital contact is specified when the equipment is de-energized, closed or stopped etc.

- . NO : NORMALLY OPEN CONTACT
- . NC : NORMALLY CLOSED CONTACT

## DESCRIPTION and USER'S GUIDE for IO LIST

### (12) FUNCTION

The function of I/O Signal is marked in appropriate column. This column shows variable function displayed on LED of DCS.

The Function on this column refers as follows;

- C : Controlling
- I : Indicating
- R : Recording or Trending
- A : Alarm
- Z : Plant Protection
- SOE : Sequence of Event

### (13) INST TYPE

The description of Tag No.

### (14) IS/NIS

The Ex. Protection types

### (15) VALVE ACTION

Valve action(Fail Position) is specified.

### (16) LOOP TAG NO.

Loop tag number is specified.

### (17) JUNCTION BOX NO.

Junction box number is specified.

### (18) P & ID NO.

P&ID drawing number is specified.

### (19) LOGIC / LOOP NO.

Logic/Loop drawing number is specified.

### (20) REMARK

Additional information is described.



PROJECT NO. : 3944  
 MR NO. : 171  
 DOC TITLE : IO LIST (POWDER)  
 DOC NO. : 3944-VD-0171-DYP-RE-400-LST-0080  
 REV : 01

## IO LIST FOR 44C-40001A



NO	TAG NO.	SERVICE DESCRIPTION	FROM /TO	RANGE	UNIT	SIGNAL TYPE	PWR SRC	I/O TYPE	CONT -ACT	FUNCTION						INST TYPE	IS / NIS	JUNCTION BOX NO.	P&ID NO.	REMARK
										C	I	R	A	Z	SOE					
<b>44C-40001A</b>																				
1	44 PT - 40010 03	INLET PRESSURE	FLD / DCS	-1 - 1	bar.g	4~20mA	I	AI	-		O		O			PRESSURE TRANSMITTER	IS	PFJBIA-40060I	40001	
2	44 TT - 40010 56	OIL TEMPERATURE	FLD / DCS	-50 - 300	°C	4~20mA	I	AI	-		O		O			TEMPERATURE TRANSMITTER	IS	PFJBIA-40060I	40001	
3	44 PT - 40010 54	OIL PRESSURE	FLD / DCS	-1 - 5	bar.g	4~20mA	I	AI	-		O		O			PRESSURE TRANSMITTER	IS	PFJBIA-40060I	40001	
4	44 PT - 40010 11	DISCHARGE PRESSURE	FLD / DCS	-1 - 5	bar.g	4~20mA	I	AI	-		O		O			PRESSURE TRANSMITTER	IS	PFJBIA-40060I	40001	
5	44 TT - 40010 57	DISCHARGE TEMPERATURE	FLD / DCS	-50 - 300	°C	4~20mA	I	AI	-		O		O			TEMPERATURE TRANSMITTER	IS	PFJBIA-40060I	40001	
6	44 TT - 40010 01	ENCLOSURE TEMPERATURE	FLD / DCS	-50 - 300	°C	4~20mA	I	AI	-		O					TEMPERATURE TRANSMITTER	IS	PFJBIA-40060I	40001	
7	44 TE - 40010 61 A	WINDING RTD PHASE A SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
8	44 TE - 40010 61 B	WINDING RTD PHASE A SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
9	44 TE - 40010 62 A	WINDING RTD PHASE B SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
10	44 TE - 40010 62 B	WINDING RTD PHASE B SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
11	44 TE - 40010 63 A	WINDING RTD PHASE C SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
12	44 TE - 40010 63 B	WINDING RTD PHASE C SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
13	44 TE - 40010 64 A	DRIVE END BEARING TEMPERATURE	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
14	44 TE - 40010 64 B	NON-DRIVE END BEARING TEMPERATURE	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
	44 PB - 40010 01	COMPRESSOR START BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-4001010	40001	
	44 PB - 40010 02	COMPRESSOR STOP BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-4001010	40001	
	44 PB - 40010 03	COMPRESSOR LAMP TEST BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-4001010	40001	
	44 XI - 40010 01	COMPRESSOR RUNNING LAMP	LPS / LPS	-	-	24VDC	-	DO	-							LAMP	NIS	44LCP-4001010	40001	
	44 XI - 40010 02	COMPRESSOR FAULT LAMP	LPS / LPS	-	-	24VDC	-	DO	-							LAMP	NIS	44LCP-4001010	40001	



PROJECT NO. : 3944  
 MR NO. : 171  
 DOC TITLE : IO LIST (POWDER)  
 DOC NO. : 3944-VD-0171-DYP-RE-400-LST-0080  
 REV : 01

**IO LIST  
 FOR  
 44C-40001B**



NO	TAG NO.	SERVICE DESCRIPTION	FROM /TO	RANGE	UNIT	SIGNAL TYPE	PWR SRC	I/O TYPE	CONT -ACT	FUNCTION						INST TYPE	IS / NIS	JUNCTION BOX NO.	P&ID NO.	REMARK
										C	I	R	A	Z	SOE					
<b>44C-40001B</b>																				
1	44 PT - 40020 03	INLET PRESSURE	FLD / DCS	-1 - 1	bar.g	4~20mA	I	AI	-							PRESSURE TRANSMITTER	IS	PFJBIA-40061I	40001	
2	44 TT - 40020 56	OIL TEMPERATURE	FLD / DCS	-50 - 300	°C	4~20mA	I	AI	-							TEMPERATURE TRANSMITTER	IS	PFJBIA-40061I	40001	
3	44 PT - 40020 05	OIL PRESSURE	FLD / DCS	-1 - 5	bar.g	4~20mA	I	AI	-							PRESSURE TRANSMITTER	IS	PFJBIA-40061I	40001	
4	44 PT - 40020 01	DISCHARGE PRESSURE	FLD / DCS	-1 - 5	bar.g	4~20mA	I	AI	-							PRESSURE TRANSMITTER	IS	PFJBIA-40061I	40001	
5	44 TT - 40020 57	DISCHARGE TEMPERATURE	FLD / DCS	-50 - 300	°C	4~20mA	I	AI	-							TEMPERATURE TRANSMITTER	IS	PFJBIA-40061I	40001	
6	44 TT - 40020 01	ENCLOSURE TEMPERATURE	FLD / DCS	-50 - 300	°C	4~20mA	I	AI	-							TEMPERATURE TRANSMITTER	IS	PFJBIA-40061I	40001	
7	44 TE - 40020 61 A	WINDING RTD PHASE A SLOT 1	FLD / MCC	X-Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
8	44 TE - 40020 61 B	WINDING RTD PHASE A SLOT 2	FLD / MCC	X-Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
9	44 TE - 40020 62 A	WINDING RTD PHASE B SLOT 1	FLD / MCC	X-Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
10	44 TE - 40020 62 B	WINDING RTD PHASE B SLOT 2	FLD / MCC	X-Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
11	44 TE - 40020 63 A	WINDING RTD PHASE C SLOT 1	FLD / MCC	X-Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
12	44 TE - 40020 63 B	WINDING RTD PHASE C SLOT 2	FLD / MCC	X-Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
13	44 TE - 40020 64 A	DRIVE END BEARING TEMPERATURE	FLD / MCC	X-Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
14	44 TE - 40020 64 B	NON-DRIVE END BEARING TEMPERATURE	FLD / MCC	X-Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
	44 PB - 40020 04	COMPRESSOR START BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-4002010	40001	
	44 PB - 40020 05	COMPRESSOR STOP BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-4002010	40001	
	44 PB - 40020 06	COMPRESSOR LAMP TEST BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-4002010	40001	
	44 XI - 40020 03	COMPRESSOR RUNNING LAMP	LPS / LPS	-	-	24VDC	-	DO	-							LAMP	NIS	44LCP-4002010	40001	
	44 XI - 40020 04	COMPRESSOR FAULT LAMP	LPS / LPS	-	-	24VDC	-	DO	-							LAMP	NIS	44LCP-4002010	40001	



PROJECT NO. : 3944  
 MR NO. : 171  
 DOC TITLE : IO LIST (POWDER)  
 DOC NO. : 3944-VD-0171-DYP-RE-400-LST-0080  
 REV : 01

IO LIST  
 FOR  
 44C-80001A



NO	TAG NO.	SERVICE DESCRIPTION	FROM /TO	RANGE	UNIT	SIGNAL TYPE	PWR SRC	I/O TYPE	CONT -ACT	FUNCTION						INST TYPE	IS / NIS	JUNCTION BOX NO.	P&ID NO.	REMARK
										C	I	R	A	Z	SOE					
<b>44C-80001A</b>																				
1	44 PDT - 80040 01	INLET DIFFERENTIAL PRESSURE	FLD / DCS	-1 - 1	bar	4~20mA	I	AI	-		O		O			DIFFERENTIAL PRESSURE TRANSMITTER	IS	PFJBIA-80081	40001	
2	44 PT - 80040 01	INLET PRESSURE	FLD / DCS	-1 - 1	bar.g	4~20mA	I	AI	-		O		O			PRESSURE TRANSMITTER	IS	PFJBIA-80082	40001	
3	44 TT - 80040 41	OIL TEMPERATURE	FLD / DCS	-50 - 300	°C	4~20mA	I	AI	-		O			O		TEMPERATURE TRANSMITTER	IS	PFJBIA-80083	40001	
4	44 PT - 80040 41	OIL PRESSURE	FLD / DCS	-1 - 5	bar.g	4~20mA	I	AI	-		O			O		PRESSURE TRANSMITTER	IS	PFJBIA-80084	40001	
5	44 PT - 80040 02	DISCHARGE PRESSURE	FLD / DCS	-1 - 5	bar.g	4~20mA	I	AI	-		O			O		PRESSURE TRANSMITTER	IS	PFJBIA-80085	40001	
6	44 TT - 80040 01	DISCHARGE TEMPERATURE	FLD / DCS	-50 - 300	°C	4~20mA	I	AI	-		O			O		TEMPERATURE TRANSMITTER	IS	PFJBIA-80086	40001	
7	44 TE - 80040 61 A	WINDING RTD PHASE A SLOT 1	FLD / MCC	X-Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
8	44 TE - 80040 61 B	WINDING RTD PHASE A SLOT 2	FLD / MCC	X-Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
9	44 TE - 80040 62 A	WINDING RTD PHASE B SLOT 1	FLD / MCC	X-Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
10	44 TE - 80040 62 B	WINDING RTD PHASE B SLOT 2	FLD / MCC	X-Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
11	44 TE - 80040 63 A	WINDING RTD PHASE C SLOT 1	FLD / MCC	X-Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
12	44 TE - 80040 63 B	WINDING RTD PHASE C SLOT 2	FLD / MCC	X-Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
13	44 TE - 80040 64 A	DRIVE END BEARING TEMPERATURE	FLD / MCC	X-Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
14	44 TE - 80040 64 B	NON-DRIVE END BEARING TEMPERATURE	FLD / MCC	X-Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
	44 PB - 80040 01	COMPRESSOR START BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-8004011	40001	
	44 PB - 80040 02	COMPRESSOR STOP BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-8004011	40001	
	44 PB - 80040 03	COMPRESSOR LAMP TEST BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-8004011	40001	
	44 XI - 80040 01	COMPRESSOR RUNNING LAMP	LPS / LPS	-	-	24VDC	-	DO	-							LAMP	NIS	44LCP-8004011	40001	
	44 XI - 80040 02	COMPRESSOR FAULT LAMP	LPS / LPS	-	-	24VDC	-	DO	-							LAMP	NIS	44LCP-8004011	40001	



PROJECT NO. : 3944  
 MR NO. : 171  
 DOC TITLE : IO LIST (POWDER)  
 DOC NO. : 3944-VD-0171-DYP-RE-400-LST-0080  
 REV : 01

IO LIST  
 FOR  
 44C-80001B



NO	TAG NO.	SERVICE DESCRIPTION	FROM /TO	RANGE	UNIT	SIGNAL TYPE	PWR SRC	I/O TYPE	CONT -ACT	FUNCTION						INST TYPE	IS / NIS	JUNCTION BOX NO.	P&ID NO.	REMARK
										C	I	R	A	Z	SOE					
<b>44C-80001B</b>																				
1	44 PDT - 80040 02	INLET DIFFERENTIAL PRESSURE	FLD / DCS	-1 - 1	bar	4~20mA	I	AI	-		O	O			DIFFERENTIAL PRESSURE TRANSMITTER	IS	PFJBIA-80082	40001		
2	44 PT - 80040 03	INLET PRESSURE	FLD / DCS	-1 - 1	bar.g	4~20mA	I	AI	-		O	O			PRESSURE TRANSMITTER	IS	PFJBIA-80082	40001		
3	44 TT - 80040 42	OIL TEMPERATURE	FLD / DCS	-50 - 300	°C	4~20mA	I	AI	-		O		O		TEMPERATURE TRANSMITTER	IS	PFJBIA-80082	40001		
4	44 PT - 80040 42	OIL PRESSURE	FLD / DCS	-1 - 5	bar.g	4~20mA	I	AI	-		O		O		PRESSURE TRANSMITTER	IS	PFJBIA-80082	40001		
5	44 PT - 80040 04	DISCHARGE PRESSURE	FLD / DCS	-1 - 5	bar.g	4~20mA	I	AI	-		O		O		PRESSURE TRANSMITTER	IS	PFJBIA-80082	40001		
6	44 TT - 80040 03	DISCHARGE TEMPERATURE	FLD / DCS	-50 - 300	°C	4~20mA	I	AI	-		O		O		TEMPERATURE TRANSMITTER	IS	PFJBIA-80082	40001		
7	44 TE - 80040 65 A	WINDING RTD PHASE A SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
8	44 TE - 80040 65 B	WINDING RTD PHASE A SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
9	44 TE - 80040 66 A	WINDING RTD PHASE B SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
10	44 TE - 80040 66 B	WINDING RTD PHASE B SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
11	44 TE - 80040 67 A	WINDING RTD PHASE C SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
12	44 TE - 80040 67 B	WINDING RTD PHASE C SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
13	44 TE - 80040 68 A	DRIVE END BEARING TEMPERATURE	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
14	44 TE - 80040 68 B	NON-DRIVE END BEARING TEMPERATURE	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
	44 PB - 80040 04	COMPRESSOR START BUTTON	LPS / LPS	-	-	24VDC	-	DI	-						PUSHBUTTON	NIS	44LCP-8004021	40001		
	44 PB - 80040 05	COMPRESSOR STOP BUTTON	LPS / LPS	-	-	24VDC	-	DI	-						PUSHBUTTON	NIS	44LCP-8004021	40001		
	44 PB - 80040 06	COMPRESSOR LAMP TEST BUTTON	LPS / LPS	-	-	24VDC	-	DI	-						PUSHBUTTON	NIS	44LCP-8004021	40001		
	44 XI - 80040 03	COMPRESSOR RUNNING LAMP	LPS / LPS	-	-	24VDC	-	DO	-						LAMP	NIS	44LCP-8004021	40001		
	44 XI - 80040 04	COMPRESSOR FAULT LAMP	LPS / LPS	-	-	24VDC	-	DO	-						LAMP	NIS	44LCP-8004021	40001		



PROJECT NO. : 3944  
 MR NO. : 171  
 DOC TITLE : IO LIST (POWDER)  
 DOC NO. : 3944-VD-0171-DYP-RE-400-LST-0080  
 REV : 01

IO LIST  
 FOR  
 44C-80002A



NO	TAG NO.	SERVICE DESCRIPTION	FROM /TO	RANGE	UNIT	SIGNAL TYPE	PWR SRC	I/O TYPE	CONT -ACT	FUNCTION						INST TYPE	IS / NIS	JUNCTION BOX NO.	P&ID NO.	REMARK
										C	I	R	A	Z	SOE					
<b>44C-80002A</b>																				
1	44 PDT - 80040 03	INLET DIFFERENTIAL PRESSURE	FLD / DCS	-1 - 1	bar	4~20mA	I	AI	-		O	O			DIFFERENTIAL PRESSURE TRANSMITTER	IS	PFJBIA-80083	40001		
2	44 PT - 80040 05	INLET PRESSURE	FLD / DCS	-1 - 1	bar.g	4~20mA	I	AI	-		O	O			PRESSURE TRANSMITTER	IS	PFJBIA-80083	40001		
3	44 PT - 80040 06	DISCHARGE PRESSURE	FLD / DCS	-1 - 5	bar.g	4~20mA	I	AI	-		O	O			PRESSURE TRANSMITTER	IS	PFJBIA-80083	40001		
4	44 TT - 80040 05	DISCHARGE TEMPERATURE	FLD / DCS	-50 - 300	°C	4~20mA	I	AI	-		O				PRESSURE TRANSMITTER	IS	PFJBIA-80083	40001		
5	44 TE - 80040 69 A	WINDING RTD PHASE A SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
6	44 TE - 80040 69 B	WINDING RTD PHASE A SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
7	44 TE - 80040 70 A	WINDING RTD PHASE B SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
8	44 TE - 80040 70 B	WINDING RTD PHASE B SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
9	44 TE - 80040 71 A	WINDING RTD PHASE C SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
10	44 TE - 80040 71 B	WINDING RTD PHASE C SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
11	44 TE - 80040 72 A	DRIVE END BEARING TEMPERATURE	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
12	44 TE - 80040 72 B	NON-DRIVE END BEARING TEMPERATURE	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
13	44 PB - 80040 07	ROOTS BLOWER START BUTTON	LPS / LPS	-	-	24VDC	-	DI	-						PUSHBUTTON	NIS	44LCP-8004031	40001		
14	44 PB - 80040 08	ROOTS BLOWER STOP BUTTON	LPS / LPS	-	-	24VDC	-	DI	-						PUSHBUTTON	NIS	44LCP-8004031	40001		
	44 PB - 80040 09	ROOTS BLOWER LAMP TEST BUTTON	LPS / LPS	-	-	24VDC	-	DI	-						PUSHBUTTON	NIS	44LCP-8004031	40001		
	44 XI - 80040 05	ROOTS BLOWER RUNNING LAMP	LPS / LPS	-	-	24VDC	-	DO	-						LAMP	NIS	44LCP-8004031	40001		
	44 XI - 80040 06	ROOTS BLOWER FAULT LAMP	LPS / LPS	-	-	24VDC	-	DO	-						LAMP	NIS	44LCP-8004031	40001		



PROJECT NO. : 3944  
 MR NO. : 171  
 DOC TITLE : IO LIST (POWDER)  
 DOC NO. : 3944-VD-0171-DYP-RE-400-LST-0080  
 REV : 01

**IO LIST  
 FOR  
 44C-80002B**



NO	TAG NO.	SERVICE DESCRIPTION	FROM /TO	RANGE	UNIT	SIGNAL TYPE	PWR SRC	I/O TYPE	CONT -ACT	FUNCTION						INST TYPE	IS / NIS	JUNCTION BOX NO.	P&ID NO.	REMARK
										C	I	R	A	Z	SOE					
<b>44C-80002B</b>																				
1	44 PDT - 80040 04	INLET DIFFERENTIAL PRESSURE	FLD / DCS	-1 - 1	bar	4~20mA	I	AI	-			O				DIFFERENTIAL PRESSURE TRANSMITTER	IS	PFJBIA-80084	40001	
2	44 PT - 80040 09	INLET PRESSURE	FLD / DCS	-1 - 1	bar.g	4~20mA	I	AI	-			O				PRESSURE TRANSMITTER	IS	PFJBIA-80084	40001	
3	44 PT - 80040 10	DISCHARGE PRESSURE	FLD / DCS	-1 - 5	bar.g	4~20mA	I	AI	-			O				PRESSURE TRANSMITTER	IS	PFJBIA-80084	40001	
4	44 TT - 80040 07	DISCHARGE TEMPERATURE	FLD / DCS	-50 - 300	bar.g	4~20mA	I	AI	-			O				PRESSURE TRANSMITTER	IS	PFJBIA-80084	40001	
5	44 TE - 80040 73 A	WINDING RTD PHASE A SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
6	44 TE - 80040 73 B	WINDING RTD PHASE A SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
7	44 TE - 80040 74 A	WINDING RTD PHASE B SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
8	44 TE - 80040 74 B	WINDING RTD PHASE B SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
9	44 TE - 80040 75 A	WINDING RTD PHASE C SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
10	44 TE - 80040 75 B	WINDING RTD PHASE C SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
11	44 TE - 80040 76 A	DRIVE END BEARING TEMPERATURE	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
12	44 TE - 80040 76 B	NON-DRIVE END BEARING TEMPERATURE	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
13	44 PB - 80040 10	COMPRESSOR START BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-8004041	40001	
14	44 PB - 80040 11	ROOTS BLOWER STOP BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-8004041	40001	
	44 PB - 80040 12	ROOTS BLOWER LAMP TEST BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-8004041	40001	
	44 XI - 80040 07	ROOTS BLOWER RUNNING LAMP	LPS / LPS	-	-	24VDC	-	DO	-							LAMP	NIS	44LCP-8004041	40001	
	44 XI - 80040 08	ROOTS BLOWER FAULT LAMP	LPS / LPS	-	-	24VDC	-	DO	-							LAMP	NIS	44LCP-8004041	40001	



PROJECT NO. : 3944  
 MR NO. : 171  
 DOC TITLE : IO LIST (POWDER)  
 DOC NO. : 3944-VD-0171-DYP-RE-400-LST-0080  
 REV : 01

IO LIST  
 FOR  
 44C-80004A



NO	TAG NO.	SERVICE DESCRIPTION	FROM /TO	RANGE	UNIT	SIGNAL TYPE	PWR SRC	I/O TYPE	CONT -ACT	FUNCTION						INST TYPE	IS / NIS	JUNCTION BOX NO.	P&ID NO.	REMARK
										C	I	R	A	Z	SOE					
<b>44C-80004A</b>																				
1	44 PDT - 80040 05	INLET DIFFERENTIAL PRESSURE	FLD / DCS	-1 - 1	bar	4~20mA	I	AI	-		O		O			DIFFERENTIAL PRESSURE TRANSMITTER	IS	PFJBIA-80085	40001	
2	44 PT - 80040 13	INLET PRESSURE	FLD / DCS	-1 - 1	bar.g	4~20mA	I	AI	-		O		O			PRESSURE TRANSMITTER	IS	PFJBIA-80085	40001	
3	44 TT - 80040 43	OIL TEMPERATURE	FLD / DCS	-50 - 300	°C	4~20mA	I	AI	-		O			O		TEMPERATURE TRANSMITTER	IS	PFJBIA-80085	40001	
4	44 PT - 80040 43	OIL PRESSURE	FLD / DCS	-1 - 5	bar.g	4~20mA	I	AI	-		O			O		PRESSURE TRANSMITTER	IS	PFJBIA-80085	40001	
5	44 PT - 80040 14	DISCHARGE PRESSURE	FLD / DCS	-1 - 5	bar.g	4~20mA	I	AI	-		O			O		PRESSURE TRANSMITTER	IS	PFJBIA-80085	40001	
6	44 TT - 80040 09	DISCHARGE TEMPERATURE	FLD / DCS	-50 - 300	°C	4~20mA	I	AI	-		O			O		TEMPERATURE TRANSMITTER	IS	PFJBIA-80085	40001	
7	44 TE - 80040 77 A	WINDING RTD PHASE A SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
8	44 TE - 80040 77 B	WINDING RTD PHASE A SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
9	44 TE - 80040 78 A	WINDING RTD PHASE B SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
10	44 TE - 80040 78 B	WINDING RTD PHASE B SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
11	44 TE - 80040 79 A	WINDING RTD PHASE C SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
12	44 TE - 80040 79 B	WINDING RTD PHASE C SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
13	44 TE - 80040 80 A	DRIVE END BEARING TEMPERATURE	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
14	44 TE - 80040 80 B	NON-DRIVE END BEARING TEMPERATURE	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
	44 PB - 80040 13	COMPRESSOR START BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-8004051	40001	
	44 PB - 80040 14	COMPRESSOR STOP BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-8004051	40001	
	44 PB - 80040 15	COMPRESSOR LAMP TEST BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-8004051	40001	
	44 XI - 80040 09	COMPRESSOR RUNNING LAMP	LPS / LPS	-	-	24VDC	-	DO	-							LAMP	NIS	44LCP-8004051	40001	
	44 XI - 80040 10	COMPRESSOR FAULT LAMP	LPS / LPS	-	-	24VDC	-	DO	-							LAMP	NIS	44LCP-8004051	40001	



PROJECT NO. : 3944  
 MR NO. : 171  
 DOC TITLE : IO LIST (POWDER)  
 DOC NO. : 3944-VD-0171-DYP-RE-400-LST-0080  
 REV : 01

IO LIST  
 FOR  
 44C-80004B



NO	TAG NO.	SERVICE DESCRIPTION	FROM /TO	RANGE	UNIT	SIGNAL TYPE	PWR SRC	I/O TYPE	CONT -ACT	FUNCTION						INST TYPE	IS / NIS	JUNCTION BOX NO.	P&ID NO.	REMARK
										C	I	R	A	Z	SOE					
<b>44C-80004B</b>																				
1	44 PDT - 80040 06	INLET DIFFERENTIAL PRESSURE	FLD / DCS	-1 - 1	bar	4~20mA	I	AI	-		O	O			DIFFERENTIAL PRESSURE TRANSMITTER	IS	44AJB-80004B	40001		
2	44 PT - 80040 16	INLET PRESSURE	FLD / DCS	-1 - 1	bar.g	4~20mA	I	AI	-		O	O			PRESSURE TRANSMITTER	IS	PFJBIA-80086	40001		
3	44 TT - 80040 44	OIL TEMPERATURE	FLD / DCS	-50 - 300	°C	4~20mA	I	AI	-		O		O		TEMPERATURE TRANSMITTER	IS	PFJBIA-80086	40001		
4	44 PT - 80040 44	OIL PRESSURE	FLD / DCS	-1 - 5	bar.g	4~20mA	I	AI	-		O		O		PRESSURE TRANSMITTER	IS	PFJBIA-80086	40001		
5	44 PT - 80040 17	DISCHARGE PRESSURE	FLD / DCS	-1 - 5	bar.g	4~20mA	I	AI	-		O		O		PRESSURE TRANSMITTER	IS	PFJBIA-80086	40001		
6	44 TT - 80040 11	DISCHARGE TEMPERATURE	FLD / DCS	-50 - 300	°C	4~20mA	I	AI	-		O		O		TEMPERATURE TRANSMITTER	IS	PFJBIA-80086	40001		
7	44 TE - 80040 81 A	WINDING RTD PHASE A SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
8	44 TE - 80040 81 B	WINDING RTD PHASE A SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
9	44 TE - 80040 82 A	WINDING RTD PHASE B SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
10	44 TE - 80040 82 B	WINDING RTD PHASE B SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
11	44 TE - 80040 83 A	WINDING RTD PHASE C SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
12	44 TE - 80040 83 B	WINDING RTD PHASE C SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
13	44 TE - 80040 84 A	DRIVE END BEARING TEMPERATURE	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
14	44 TE - 80040 84 B	NON-DRIVE END BEARING TEMPERATURE	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-						RTD	NIS	-	40001		
	44 PB - 80040 16	COMPRESSOR START BUTTON	LPS / LPS	-	-	24VDC	-	DI	-						PUSHBUTTON	NIS	44LCP-8004061	40001		
	44 PB - 80040 17	COMPRESSOR STOP BUTTON	LPS / LPS	-	-	24VDC	-	DI	-						PUSHBUTTON	NIS	44LCP-8004061	40001		
	44 PB - 80040 18	COMPRESSOR LAMP TEST BUTTON	LPS / LPS	-	-	24VDC	-	DI	-						PUSHBUTTON	NIS	44LCP-8004061	40001		
	44 XI - 80040 11	COMPRESSOR RUNNING LAMP	LPS / LPS	-	-	24VDC	-	DO	-						LAMP	NIS	44LCP-8004061	40001		
	44 XI - 80040 12	COMPRESSOR FAULT LAMP	LPS / LPS	-	-	24VDC	-	DO	-						LAMP	NIS	44LCP-8004061	40001		



PROJECT NO. : 3944  
 MR NO. : 171  
 DOC TITLE : IO LIST (POWDER)  
 DOC NO. : 3944-VD-0171-DYP-RE-400-LST-0080  
 REV : 01

IO LIST  
 FOR  
 44C-80005A



NO	TAG NO.	SERVICE DESCRIPTION	FROM /TO	RANGE	UNIT	SIGNAL TYPE	PWR SRC	I/O TYPE	CONT -ACT	FUNCTION						INST TYPE	IS / NIS	JUNCTION BOX NO.	P&ID NO.	REMARK
										C	I	R	A	Z	SOE					
<b>44C-80005A</b>																				
1	44 PDT - 80050 01	INLET DIFFERENTIAL PRESSURE	FLD / DCS	-1 - 1	bar	4~20mA	I	AI	-		O		O			DIFFERENTIAL PRESSURE TRANSMITTER	IS	PFJBIA-80087	40001	
2	44 PT - 80050 01	INLET PRESSURE	FLD / DCS	-1 - 1	bar.g	4~20mA	I	AI	-		O		O			PRESSURE TRANSMITTER	IS	PFJBIA-80087	40001	
3	44 TT - 80050 41	OIL TEMPERATURE	FLD / DCS	-50 - 300	°C	4~20mA	I	AI	-		O			O		TEMPERATURE TRANSMITTER	IS	PFJBIA-80087	40001	
4	44 PT - 80050 41	OIL PRESSURE	FLD / DCS	-1 - 5	bar.g	4~20mA	I	AI	-		O			O		PRESSURE TRANSMITTER	IS	PFJBIA-80087	40001	
5	44 PT - 80050 02	DISCHARGE PRESSURE	FLD / DCS	-1 - 5	bar.g	4~20mA	I	AI	-		O			O		PRESSURE TRANSMITTER	IS	PFJBIA-80087	40001	
6	44 TT - 80050 01	DISCHARGE TEMPERATURE	FLD / DCS	-50 - 300	°C	4~20mA	I	AI	-		O			O		TEMPERATURE TRANSMITTER	IS	PFJBIA-80087	40001	
7	44 TE - 80050 61 A	WINDING RTD PHASE A SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
8	44 TE - 80050 61 B	WINDING RTD PHASE A SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
9	44 TE - 80050 62 A	WINDING RTD PHASE B SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
10	44 TE - 80050 62 B	WINDING RTD PHASE B SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
11	44 TE - 80050 63 A	WINDING RTD PHASE C SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
12	44 TE - 80050 63 B	WINDING RTD PHASE C SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
13	44 TE - 80050 64 A	DRIVE END BEARING TEMPERATURE	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
14	44 TE - 80050 64 B	NON-DRIVE END BEARING TEMPERATURE	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
	44 PB - 80050 01	COMPRESSOR START BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-8004071	40001	
	44 PB - 80050 02	COMPRESSOR STOP BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-8004071	40001	
	44 PB - 80050 03	COMPRESSOR LAMP TEST BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-8004071	40001	
	44 XI - 80050 01	COMPRESSOR RUNNING LAMP	LPS / LPS	-	-	24VDC	-	DO	-							LAMP	NIS	44LCP-8004071	40001	
	44 XI - 80050 02	COMPRESSOR FAULT LAMP	LPS / LPS	-	-	24VDC	-	DO	-							LAMP	NIS	44LCP-8004071	40001	



PROJECT NO. : 3944  
 MR NO. : 171  
 DOC TITLE : IO LIST (POWDER)  
 DOC NO. : 3944-VD-0171-DYP-RE-400-LST-0080  
 REV : 01

## IO LIST FOR 44C-80005B



NO	TAG NO.	SERVICE DESCRIPTION	FROM /TO	RANGE	UNIT	SIGNAL TYPE	PWR SRC	I/O TYPE	CONT -ACT	FUNCTION						INST TYPE	IS / NIS	JUNCTION BOX NO.	P&ID NO.	REMARK
										C	I	R	A	Z	SOE					
<b>44C-80005B</b>																				
1	44 PDT - 80050 02	INLET DIFFERENTIAL PRESSURE	FLD / DCS	-1 - 1	bar	4~20mA	I	AI	-		O		O			DIFFERENTIAL PRESSURE TRANSMITTER	IS	PFJBIA-80088	40001	
2	44 PT - 80050 04	INLET PRESSURE	FLD / DCS	-1 - 1	bar.g	4~20mA	I	AI	-		O		O			PRESSURE TRANSMITTER	IS	PFJBIA-80088	40001	
3	44 TT - 80050 42	OIL TEMPERATURE	FLD / DCS	-50 - 300	°C	4~20mA	I	AI	-		O			O		TEMPERATURE TRANSMITTER	IS	PFJBIA-80088	40001	
4	44 PT - 80050 42	OIL PRESSURE	FLD / DCS	-1 - 5	bar.g	4~20mA	I	AI	-		O			O		PRESSURE TRANSMITTER	IS	PFJBIA-80088	40001	
5	44 PT - 80050 05	DISCHARGE PRESSURE	FLD / DCS	-1 - 5	bar.g	4~20mA	I	AI	-		O		O			PRESSURE TRANSMITTER	IS	PFJBIA-80088	40001	
6	44 TT - 80050 03	DISCHARGE TEMPERATURE	FLD / DCS	-50 - 300	°C	4~20mA	I	AI	-		O			O		TEMPERATURE TRANSMITTER	IS	PFJBIA-80088	40001	
7	44 TE - 80050 65 A	WINDING RTD PHASE A SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
8	44 TE - 80050 65 B	WINDING RTD PHASE A SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
9	44 TE - 80050 66 A	WINDING RTD PHASE B SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
10	44 TE - 80050 66 B	WINDING RTD PHASE B SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
11	44 TE - 80050 67 A	WINDING RTD PHASE C SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
12	44 TE - 80050 67 B	WINDING RTD PHASE C SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
13	44 TE - 80050 68 A	DRIVE END BEARING TEMPERATURE	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
14	44 TE - 80050 68 B	NON-DRIVE END BEARING TEMPERATURE	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
	44 PB - 80050 04	COMPRESSOR START BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-8004081	40001	
	44 PB - 80050 05	COMPRESSOR STOP BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-8004081	40001	
	44 PB - 80050 06	COMPRESSOR LAMP TEST BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-8004081	40001	
	44 XI - 80050 03	COMPRESSOR RUNNING LAMP	LPS / LPS	-	-	24VDC	-	DO	-							LAMP	NIS	44LCP-8004081	40001	
	44 XI - 80050 04	COMPRESSOR FAULT LAMP	LPS / LPS	-	-	24VDC	-	DO	-							LAMP	NIS	44LCP-8004081	40001	



PROJECT NO. : 3944  
 MR NO. : 171  
 DOC TITLE : IO LIST (POWDER)  
 DOC NO. : 3944-VD-0171-DYP-RE-400-LST-0080  
 REV : 04

## IO LIST FOR 44C-80005C



NO	TAG NO.	SERVICE DESCRIPTION	FROM /TO	RANGE	UNIT	SIGNAL TYPE	PWR SRC	I/O TYPE	CONT -ACT	FUNCTION						INST TYPE	IS / NIS	JUNCTION BOX NO.	P&ID NO.	REMARK
										C	I	R	A	Z	SOE					
<b>44C-80005C</b>																				
1	44 PDT - 80050 03	INLET DIFFERENTIAL PRESSURE	FLD / DCS	-1 - 1	bar	4~20mA	I	AI	-		O		O			DIFFERENTIAL PRESSURE TRANSMITTER	IS	PFJBIA-80089	40001	
2	44 PT - 80050 06	INLET PRESSURE	FLD / DCS	-1 - 1	bar.g	4~20mA	I	AI	-		O		O			PRESSURE TRANSMITTER	IS	PFJBIA-80089	40001	
3	44 TT - 80050 43	OIL TEMPERATURE	FLD / DCS	-50 - 300	°C	4~20mA	I	AI	-		O			O		TEMPERATURE TRANSMITTER	IS	PFJBIA-80089	40001	
4	44 PT - 80050 43	OIL PRESSURE	FLD / DCS	-1 - 5	bar.g	4~20mA	I	AI	-		O			O		PRESSURE TRANSMITTER	IS	PFJBIA-80089	40001	
5	44 PT - 80050 07	DISCHARGE PRESSURE	FLD / DCS	-1 - 5	bar.g	4~20mA	I	AI	-		O			O		PRESSURE TRANSMITTER	IS	PFJBIA-80089	40001	
6	44 TT - 80050 04	DISCHARGE TEMPERATURE	FLD / DCS	-50 - 300	°C	4~20mA	I	AI	-		O			O		TEMPERATURE TRANSMITTER	IS	PFJBIA-80089	40001	
7	44 TE - 80050 69 A	WINDING RTD PHASE A SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
8	44 TE - 80050 69 B	WINDING RTD PHASE A SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
9	44 TE - 80050 70 A	WINDING RTD PHASE B SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
10	44 TE - 80050 70 B	WINDING RTD PHASE B SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
11	44 TE - 80050 71 A	WINDING RTD PHASE C SLOT 1	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
12	44 TE - 80050 71 B	WINDING RTD PHASE C SLOT 2	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
13	44 TE - 80050 72 A	DRIVE END BEARING TEMPERATURE	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
14	44 TE - 80050 72 B	NON-DRIVE END BEARING TEMPERATURE	FLD / MCC	X~Y	°C	RTD	N/A	0-100Ω	-							RTD	NIS	-	40001	
	44 PB - 80050 07	COMPRESSOR START BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-8004091	40001	
	44 PB - 80050 08	COMPRESSOR STOP BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-8004091	40001	
	44 PB - 80050 09	COMPRESSOR LAMP TEST BUTTON	LPS / LPS	-	-	24VDC	-	DI	-							PUSHBUTTON	NIS	44LCP-8004091	40001	
	44 XI - 80050 05	COMPRESSOR RUNNING LAMP	LPS / LPS	-	-	24VDC	-	DO	-							LAMP	NIS	44LCP-8004091	40001	
	44 XI - 80050 06	COMPRESSOR FAULT LAMP	LPS / LPS	-	-	24VDC	-	DO	-							LAMP	NIS	44LCP-8004091	40001	